

of Science and Useful Arts

The Director

of the United States Patent and Trademark Office has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this United States

grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America, and if the invention is a process, of the right to exclude others from using, offering for sale or selling throughout the United States of America, products made by that process, for the term set forth in 35 U.s.c. 154(a)(2) or (c)(1), subject to the payment of maintenance fees as provided by 35 U.s.c. 41(b). See the Maintenance Fee Notice on the inside of the cover.



Katherine Kelly Vidal

DIRECTOR OF THE UNITED STATES PATENT AND TRADEMARK OFFICE

Maintenance Fee Notice

If the application for this patent was filed on or after December 12, 1980, maintenance fees are due three years and six months, seven years and six months, and eleven years and six months after the date of this grant, or within a grace period of six months thereafter upon payment of a surcharge as provided by law. The amount, number and timing of the maintenance fees required may be changed by law or regulation. Unless payment of the applicable maintenance fee is received in the United States Patent and Trademark Office on or before the date the fee is due or within a grace period of six months thereafter, the patent will expire as of the end of such grace period.

Patent Term Notice

If the application for this patent was filed on or after June 8, 1995, the term of this patent begins on the date on which this patent issues and ends twenty years from the filing date of the application or, if the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121, 365(c), or 386(c), twenty years from the filing date of the earliest such application ("the twenty-year term"), subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b), and any extension as provided by 35 U.S.C. 154(b) or 156 or any disclaimer under 35 U.S.C. 253.

If this application was filed prior to June 8, 1995, the term of this patent begins on the date on which this patent issues and ends on the later of seventeen years from the date of the grant of this patent or the twenty-year term set forth above for patents resulting from applications filed on or after June 8, 1995, subject to the payment of maintenance fees as provided by 35 U.S.C. 41(b) and any extension as provided by 35 U.S.C. 156 or any disclaimer under 35 U.S.C. 253.



US011787715B2

(12) United States Patent

Moulton et al.

(54) APPARATUS AND METHOD FOR RECYCLING BLACKWATER AND GREYWATER AT OIL AND GAS WELL SITES

- (71) Applicant: STALLION OILFIELD SERVICES LTD., Houston, TX (US)
- (72) Inventors: Justin Vance Moulton, Victor, ID (US); Hal D. Hingson, Carlsbad, NM (US)
- (73) Assignee: STALLION OILFIELD SERVICES LTD., Houston, TX (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 17/576,129
- (22) Filed: Jan. 14, 2022

(65) **Prior Publication Data**

US 2022/0135457 A1 May 5, 2022

Related U.S. Application Data

- (63) Continuation of application No. 16/879,250, filed on May 20, 2020, now Pat. No. 11,225,425, which is a (Continued)
- (51) Int. Cl.

C02F 3/20	(2023.01)
C02F 9/00	(2023.01)

(Continued)

(10) Patent No.: US 11,787,715 B2 (45) Date of Patent: Oct. 17, 2023

1/32 (2013.01); C02F 1/76 (2013.01); C02F 2001/007 (2013.01); C02F 2103/002 (2013.01); C02F 2103/005 (2013.01); C02F 2203/006 (2013.01);

(Continued) (58) **Field of Classification Search** None

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,807,563	А	*	4/1974	Reid, Jr.	B01D 21/0045
					210/197
4,076,617	A	*	2/1978	Bybel	C02F 1/36
					261/81

(Continued)

Primary Examiner — Chester T Barry

(74) Attorney, Agent, or Firm — MH2 TECHNOLOGY LAW GROUP LLP

(57) ABSTRACT

A bioreactor for a water treatment system includes a tank configured to receive an influent liquid, a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a downwardly-facing opening proximal to or at a bottom of the separator structure, an interior of the separator structure being in communication with the tank, external to the separator structure, at least via the opening, an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not directly into the interior of the separator structure, and an effluent outlet communicating with the interior of in the separator structure, proximal to a top of the separator structure, a relatively clean effluent liquid, in comparison to the influent liquid in the tank, exiting from the separator structure via the effluent outlet.

17 Claims, 8 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/007,495, filed on Jun. 13, 2018, now Pat. No. 10,669,177.

- (60) Provisional application No. 62/519,692, filed on Jun. 14, 2017.
- (51) Int. Cl.

B01D 21/24	(2006.01)
B01D 21/02	(2006.01)
C02F 1/00	(2023.01)
C02F 1/76	(2023.01)
C02F 103/00	(2006.01)
C02F 1/32	(2023.01)

(52) **U.S. Cl.** CPC C02F 2203/008 (2013.01); C02F 2303/04 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,650,577	А		3/1987	Hansel
4,983,285	А	*	1/1991	Nolen C02F 3/20
				210/207
5,032,276	А		7/1991	Mackrle et al.
5,191,830	А	*	3/1993	Jacobson A21B 3/132
				99/428
5,196,114	А		3/1993	Burwell
5,217,609	А	*	6/1993	Holdeman C02F 3/12
				210/197
5,221,470	А		6/1993	McKinney
5,490,935	А		2/1996	Guy
5,549,818	А		8/1996	McGrew, Jr.
5,766,459	А		6/1998	Adams, Jr.
5,770,081	А		6/1998	McKinney
5,785,854	А		7/1998	McKinney
5,874,002	А		2/1999	Cormier
6,096,203	А		8/2000	Drewery

6,106,704	Α	8/2000	Drewery
6,165,359	А	12/2000	Drewery
6,193,220	B1	2/2001	Kelly
6,200,472	B1	3/2001	Donald et al.
6,217,761	B1	4/2001	Catanzaro et al.
6,228,258	B1	5/2001	Hubbard et al.
6,280,624	B1 *	8/2001	Hermans C02F 3/26
			210/614
6,358,411	B1	3/2002	McKinney
6,406,619	B1	6/2002	Hubbard et al.
6,733,672	B2 *	5/2004	Hiatt C02F 3/302
			210/609
6,752,921	B1 *	6/2004	Kulick, III C02F 3/1273
- , - ,- ,-			210/150
6.982.033	B2	1/2006	Donald
7.067.055	B2 *	6/2006	Ruppel
1,001,000	52	0,2000	210/291
7 341 660	B1	3/2008	Guy et al
7,541,000	B2	1/2010	McKinney
7 794 592	B2 *	9/2010	Brown C02F 1/72
1,194,392	D2	72010	210/220
8 025 708	B)*	0/2011	Kigel C02E 3/12
8,023,798	D2 -	9/2011	Xiger C021 5/12
0 102 026	D1 *	2/2012	Saha C02E 2/12/7
8,125,950	DI	2/2012	Sabo C02F 5/1247
10 501 257	D1 *	12/2010	210/151 McKinger D01D 21/02
10,501,357	BI*	12/2019	McKinney B01D 21/02
2010/0112/00	AI*	5/2010	Shaaltiel C12M 23/00
2010/0200511		10/2010	435/410
2010/0300544	AI	12/2010	Baldwin et al.
2011/0000862	Al*	1/2011	Semba E03F 5/14
			210/304
2011/0186491	A1	8/2011	McKinney
2014/0030555	A1*	1/2014	Winkler H01M 8/16
			429/2
2016/0016835	A1*	1/2016	McKinney C02F 9/00
			210/150
2017/0217806	A1*	8/2017	Razavi-Shirazi C02F 3/108
2017/0283291	A1	10/2017	Sabo et al.
2019/0367393	A1	12/2019	Assadi et al.

* cited by examiner













FIG. 4



FIG. 5



FIG. 6





FIG. 78

APPARATUS AND METHOD FOR RECYCLING BLACKWATER AND GREYWATER AT OIL AND GAS WELL SITES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Patent Application having Ser. No. 16/879,250, which was filed on May ¹⁰ 20, 2020 and is continuation of U.S. Patent Application having Ser. No. 16/007,495, which was filed on Jun. 13, 2018 and claims priority to U.S. Provisional Patent Application having Ser. No. 62/519,692, which was filed on Jun. 14, 2017. Each of these priority applications is incorporated ¹⁵ herein by reference in its entirety.

BACKGROUND

Clean water used by personnel performing labor at oil and 20 gas well sites is commonly delivered and stored in water tanks at the well site. Water is also needed at well sites during drilling operations for drilling fluid, also called drilling mud. The purchase, delivery, and storage of water at well sites can be a significant part of overhead associated 25 with drilling operations.

Many tasks and operations at oil and gas well sites, including drilling operations, require human labor. The presence of personnel at the well site and their water needs may vary. Most if not all personnel at well sites require the 30 use of on-site restrooms. Personnel residing at well sites over multiple days require running water for drinking, cooking, cleaning dishes, and washing clothes. Consequently, human activity at oil and gas well sites commonly results in at least two types of wastewater: blackwater and 35 greywater.

Blackwater results from restrooms and is wastewater containing feces, urine and flushwater from flush toilets or toilet paper. Greywater or sullage is generally wastewater generated in households or office buildings from streams 40 without fecal contamination, i.e. all streams except for the wastewater from toilets. Greywater may include the wastewater resulting from cleaning dishes and washing clothes. Blackwater and greywater are to be distinguished from "produced water," which term is used in the oil industry to 45 describe water that is produced as a byproduct along with the oil and gas.

Generally, blackwater and greywater resulting from human activity cannot simply be disposed of at an oil or gas well site; rather, industry practice has been to collect the 50 wastewater in holding tanks and then transport it to remote locations for treatment. Often municipal water treatment facilities are contracted to receive and treat blackwater and greywater. The cost for wastewater transport services and to compensate municipal wastewater treatment facilities can 55 significantly increase overhead for well site operations.

There are a number of challenges with collecting and treating blackwater and greywater. Treatment of such wastewater has often had to rely on municipal water treatment facilities or other more permanent water treatment systems. 60 Such facilities may be permanently located at great distances from remote well sites. Further, the water treatment facilities are generally not built for specific well sites or groups of well sites because of the extensive resources and costs to build them. Likewise, the tentative viability of well sites and 65 scarcity of well sites in a given group to be served make it infeasible to build permanent water treatment facilities for

specific well sites or groups of well sites. Once a water treatment facility is built, it is usually fixed to a location and cannot be transported to new sites when needed.

Also, greywater from certain greywater sources at well sites contains substantial amounts of diesel, oil, grease, cuttings, and or drilling mud. Some of these contaminants, such as diesel, kill or otherwise inhibit growth of bacteria and other microorganisms useful for the treatment of waste water.

SUMMARY

A bioreactor for a water treatment system is disclosed. The bioreactor includes a tank configured to receive an influent liquid, a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a downwardly-facing opening proximal to or at a bottom of the separator structure, an interior of the separator structure being in communication with the tank, external to the separator structure, at least via the opening, an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not directly into the interior of the separator structure, and an effluent outlet communicating with the interior of in the separator structure, proximal to a top of the separator structure, a relatively clean effluent liquid, in comparison to the influent liquid, exiting from the separator structure via the effluent outlet.

A water treatment system is also disclosed. The water treatment system includes a bioreactor including a tank configured to receive an influent liquid, a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a downwardly-facing opening proximal to or at a bottom of the separator structure, an interior of the separator structure being in communication with the tank, external to the separator structure, at least via the opening, an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not into the interior of the separator structure, and an effluent outlet communicating with the interior of in the separator structure, proximal to a top of the separator structure, a relatively clean effluent liquid, in comparison to the influent liquid, exiting from the separator structure via the effluent outlet, a filter tank in fluid communication with the second clarifier, an ultraviolet (UV) filter in fluid communication with the filter tank, and a chlorinator in fluid communication with the UV filter.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure may best be understood by referring to the following description and accompanying drawings that are used to illustrate embodiments of the invention. In the drawings:

FIG. 1 illustrates a flow diagram of a wastewater treatment system, according to an embodiment.

FIGS. 2A and 2B illustrates a plan view and an elevation view, respectively, of the wastewater treatment system, according to an embodiment.

FIG. $\mathbf{\tilde{3}}$ illustrates a perspective view of a container in which the wastewater treatment may be housed, according to an embodiment.

FIG. **4** illustrates a perspective view of a bioreactor tank, according to an embodiment.

FIG. **5** illustrates a side, elevation view of a conical clarifier, according to an embodiment.

FIG. 6 illustrates a side, cross-sectional, conceptual view of the bioreactor tank including the conical clarifier, according to an embodiment.

FIGS. **7**A and **7**B illustrate a flowchart of a method for treating wastewater, according to an embodiment.

DETAILED DESCRIPTION

The following disclosure describes several embodiments 10 for implementing different features, structures, or functions of the invention. Embodiments of components, arrangements, and configurations are described below to simplify the present disclosure; however, these embodiments are provided merely as examples and are not intended to limit the scope of the invention. Additionally, the present disclosure may repeat reference characters (e.g., numerals) and/or letters in the various embodiments and across the Figures provided herein. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship 20 between the various embodiments and/or configurations discussed in the Figures. Moreover, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also 25 include embodiments in which additional features may be formed interposing the first and second features, such that the first and second features may not be in direct contact. Finally, the embodiments presented below may be combined in any combination of ways, e.g., any element from one 30 exemplary embodiment may be used in any other exemplary embodiment, without departing from the scope of the disclosure.

Additionally, certain terms are used throughout the following description and claims to refer to particular compo-35 nents. As one skilled in the art will appreciate, various entities may refer to the same component by different names, and as such, the naming convention for the elements described herein is not intended to limit the scope of the invention, unless otherwise specifically defined herein. Fur- 40 ther, the naming convention used herein is not intended to distinguish between components that differ in name but not function. Additionally, in the following discussion and in the claims, the terms "including" and "comprising" are used in an open-ended fashion, and thus should be interpreted to 45 mean "including, but not limited to." All numerical values in this disclosure may be exact or approximate values unless otherwise specifically stated. Accordingly, various embodiments of the disclosure may deviate from the numbers, values, and ranges disclosed herein without departing from 50 the intended scope. In addition, unless otherwise provided herein, "or" statements are intended to be non-exclusive; for example, the statement "A or B" should be considered to mean "A, B, or both A and B."

FIG. 1 illustrates a flow diagram of a wastewater treat-55 ment system 100, according to an embodiment. The system 100 may receive a primary (e.g., blackwater or graywater) wastewater stream ("influent fluid") from a primary source 101. The primary influent fluid may be received from sources that are generally considered to be free from con-60 taminants that are known to kill or negatively impact growth of useful bacteria in the water treatment process (e.g., hydrocarbons such as diesel, acids, bleach, etc.). The primary source 101 may include greywater from most or all greywater sources, including from all washing machines, 65 dishwashers, showers, sinks, etc., other than the secondary or designated greywater source, in general, so long as the

greywater sources are maintained generally free from the aforementioned contaminates.

The primary influent fluid may be directed to a preclarifying assembly **102**, which may include a first settling tank for receiving waste water, and an influent water tank, among potentially other structures. One example of the first settling tank may include dimensions for holding about 1,000 gallons, 1,250 gallons, or 1,500 gallons of water. The first settling tank may include an outlet that is configured to accept influent from a point along the height of the first settling tank, proximal to the top, such that relatively clean influent is taken, rather than solids, which have settled to the bottom, or floating contaminants on the top. Fats and oils from waste water in the first settling tank rise toward the top 15 of the water and cleaner water from the middle section of the first settling tank is removed and transferred to an influent tank using gravity transfer.

A baffle having holes or slots to permit the passage of water is disposed horizontally within the first settling tank approximately adjacent to a region just below the middle region of the first settling tank. The baffle facilitates reduction of water movement between the middle region of the first settling tank where clarified water aggregates and the lower region of the first settling tank where solids can settle and accumulate. The baffle disposed in the first settling tank helps separate settled dirty water from middle clarified or partially clarified water. The first settling tank also includes a water conduit or pipe, which can be made of PVC, configured for transferring clarified or partially clarified water from the first settling tank. The PVC pipe or conduit is fluidly connected to the effluent port on the inside of the first settling tank and extends approximately halfway into the first settling tank in the middle region of the tank where the clarified or partially clarified water resides. An opening near the end of the PVC pipe at the middle region of the first settling tank allows clarified water to exit the first settling tank through the PVC pipe. Clarified water traveling through the PVC pipes passes through the effluent port and into flexible rubber hose that couples the first settling tank with the influent tank. As water is pumped into the first settling tank, hydraulics force clarified water through the PVC pipe, the effluent port, and the flexible rubber hose so that the clarified or partially clarified water transfers into the influent tank.

The influent tank may also made of a light polycarbonate plastic and is used for holding water received from the first settling tank until sufficient water has been received for delivery to the bioreactor tank. The influent tank can be a doorway tank which can be configured with a range of dimensions for holding water ranging from about 50 gallons to about 500 gallons of water. In an embodiment, the influent tank is a 250-gallon doorway tank. The influent tank may be configured with a float-switch that triggers a pump when the water level reaches a desired level in the influent tank. When water diminished of fats and oils reaches a desired level in the influent tank, the float-switch triggers the influent tank pump, and water is pumped from the influent tank through water conduits into a bioreactor tank configured for combined aeration and clarifying.

As mentioned above, the influent fluid received from the influent tank may be directed to the bioreactor tank (also referred to herein as a bioreactor) **104**, which may include a combination of a conical clarifier **106** and an aerator tank **105**. In particular, the conical clarifier **106** may be positioned within the aerator tank **105**, as will be described in greater detail below. The bioreactor tank **104** is configured with appropriate dimensions for increased water surface area to

5

reduce the rate at which water levels change. The bioreactor tank is a vertical tank made of a light polycarbonate plastic polymer configured with a range of dimensions for holding water ranging from about 1,000 gallons to about 1,700 gallons of water. Further, the mixed liquor (activated solids and fluids) in the bioreactor tank **104** may be held at a pH between about 7 and about 8. Further, the dissolved oxygen levels in the mixed liquor in the aerator tank **105** may range from about 1 mgL to about 5 mgL.

Solids settleability characteristics within the aerated mix- 10 ture in the bioreactor tank **104** can be measured using a settleability test. A 15-minute settleability test can be run using a (e.g., 1,000 mL) beaker. The bioreactor **104** may be properly operated where settlement measurements are between about 150 mgL and 600 mgL. In an embodiment, 15 the optimal settlement level measured by the 15 minute settleability test is between about 200 mgL and 300 mgL when other parameters are within optimal ranges. The settlement level range may fluctuate depending on bioreactor water temperatures. Bio-augmentation nutrient levels 20 will vary depending on the life forms seen under the microscope.

Water in the bioreactor tank may be maintained at between 70 and 95 degrees Fahrenheit to promote bacteria growth. The water temperature within the bioreactor tank 25 **104** can be moderated in several ways. Water heaters with thermal controls can be disposed within the water in the bioreactor tank **104**. Likewise, air temperature within the insulated metal storage shipping container can be moderated, which in turn helps control or buffer the water temoperature within the bioreactor tank **104**. Air temperature within a container in which the bioreactor tank **104** is held (discussed below with reference to FIG. **3**) may be controlled using portable air conditioning or heating units with thermal controls. 35

The bioreactor tank **104** may include an effluent outlet, which removes relatively clean effluent fluid (as compared to the influent fluid) from within the conical clarifier **106**, and directs the effluent fluid to a second clarifier **108**, and then to a post-clarifying assembly **110**. As will be described 40 in greater detail below, the post-clarifying assembly **110** may include one or more filter tanks, chlorinators, ultraviolet (UV) filters, transfer tanks, pumps, etc. After passing through the post-clarifying assembly **110**, the effluent fluid may be pumped into a wastewater tank **112**. The effluent 45 fluid in the wastewater tank **112** may then be combined with wastewater from a secondary source **114** for use in oil rig operations, such as drilling fluid, boiler water, pressure washing fluid, etc.

In some embodiments, the secondary source may be 50 greywater that is potentially contaminated with hydrocarbons or other compositions that may harm bacteria, e.g., in the bioreactor tank **104**, and is thus not treated through the system **100** with the influent fluid from the primary source **101**. As such, greywater processing is separated so that 55 greywater from a primary source may be treated separately from a secondary or designated greywater source. The secondary or designated washer for washing rig hands' clothes and materials soiled with contaminants that can kill 60 or inhibit growth of useful bacteria and other microorganisms. The greywater from the secondary or designated greywater source of designated greywater source includes waste water for the secondary or designated with contaminants that can kill 60 or inhibit growth of useful bacteria and other microorganisms. The greywater from the secondary or designated greywater source may include substantial amounts of diesel, oil, grease, cuttings, and or drilling mud.

Turning now to FIGS. 2A and 2B, there is shown a plan 65 view and an elevation view, respectively, of the wastewater treatment system 100, according to an embodiment. As

6

shown, the system 100 includes the bioreactor tank 104. FIGS. 2A and 2B also depict additional elements of the post-clarifying assembly 110, namely, in this embodiment, a second clarifier 200, a filter tank 202, a UV filter 204, a chlorinator 206, a transfer tank 208, and a wastewater tank 210. In a specific embodiment, the post-clarifying assembly 110 also includes one or more flexible pipes (e.g., pipe 212), which connect the elements together, facilitating the mobility of the system 100.

The second clarifier **200** may be a vertical tank made of a light polycarbonate plastic polymer. The second clarifier **200** may be configured with a range of dimensions for holding between about 300 and about 500 gallons of water. The inside bottom of the second clarifier **200** may be cone-shaped and funnel toward the center where a solids removal port is disposed. Solids settled in the second clarifier **200** may be removed from the tank by via the solids removal port.

Water clarified in the second clarifier 200 may be conveved using gravity and/or hydraulics through water conduits to the filter tank 202, which may be a gravity filter tank **202**. The gravity filter tank **202** may be a vertical tank made of a light and durable polycarbonate plastic. The inside bottom of the gravity filter tank 202 may be cone-shaped and funnel toward the center where a solids removal port is disposed. Solids accumulating in the bottom of the gravity filter tank 202 may be removed from the tank through the solids removal port. The gravity filter tank 202 may be configured with a range of dimensions for holding from between about 40 and about 100 gallons of water. The gravity filter tank 202 may use various filter media. Crushed pumice works may be employed as the gravity filter media for removing residual particles without clogging the gravity filter. It is understood that other filter media such as sand or 35 GAC could also be used in the gravity filter tank 202.

The transfer tank **208** may be a cylindrical vertical tank and is made of a light and durable polycarbonate plastic. The transfer tank **208** may be configured with a range of dimensions for holding from about 200 gallons and 350 gallons of water. The transfer tank **208** may be configured with a float-switch that triggers a pump when the water level reaches a desired level in the transfer tank. Water is then pumped from the transfer tank **208** to a rig tank or day tank. Treated water conveyed from the transfer tank **208** to the rig tank or day tank can then be used for other operations at the well site, such as drilling operations, pressure washing the rig, or for boilers to heat the rig. The rig tanks/day tanks may hold from about 40,000 gallons to about 80,000 gallons of water.

The system 100 may also include a freshwater holding assembly 250, which may include filters, pumps, tanks, etc., as desired. However, the freshwater holding assembly 250 may not be in direct communication with the other elements of the system 100. In particular, the system 100, including the freshwater holding assembly 250 may be conveniently stored and mobile within a container, such as the container **350** shown in FIG. **3**, along with at least some of the other tanks of the system 100.

Typically, water treatment systems in oil rigs may include multiple such containers; however, rig area is valuable. Embodiments of the present system **100** may fit in a single container **350**, not only increasing mobility, but also minimizing the footprint of the system **100**. In an embodiment, the container **350** may be metal, and configured as a standard shipping container. The internal storage area of the metal storage/shipping container **350** may be divided so that there is an area devoted to the storage and transfer of fresh water 5

(e.g., clean water transported to the well site for use by well site personnel), and an area devoted to the primary and secondary segments of the water treatment system. The area within the metal storage container devoted to the primary and secondary segments of the water treatment system may extend approximately 24 feet along the length of the inside of the metal storage container and be divided by a wall configured between the water treatment area and the fresh water storage area. The fresh water storage area is disposed on the other side of the wall within the storage container opposite the water treatment area. The fresh water storage area may extend approximately twenty feet along the length of the inside of the storage container on the other side of the wall opposite the water treatment area.

A plurality of polycarbonate plastic water tanks are disposed within the water storage area. For example, four fresh water tanks may be disposed in the fresh water storage area with each tank having dimensions of about 88 inches high by about 88 inches long by about 44 inches wide. Further, the 20 first settling tank may be disposed outside of the metal storage container adjacent to the influent water tank.

FIG. 4 illustrates a perspective view of the bioreactor tank 104, showing the aerator tank 105 and the conical clarifier 106 positioned therein. The bioreactor tank 104 may include 25 an inlet port 405, which may be offset from the conical clarifier 106, so as to avoid influent being received directly from the inlet port 405 to the interior of the conical clarifier 106.

The conical clarifier **106** is relatively small in comparison 30 to the aerator tank **105**. In some embodiments, the conical clarifier **106** occupies no more than $\frac{1}{8}$ th of the volume of the aerator tank **105**. Moreover, FIG. **4** illustrates the aerator tank **105** as being clear, and in some embodiments, it is made of a clear or translucent polymer material (e.g., polycarbon-35 ate), which provides a quick reference as to the operating state of the bioreactor tank **104**. Indeed, any of the aforementioned tanks discussed herein may be fabricated using a clear polymer. In other embodiments, the bioreactor tank **104** (and/or any of the other tanks discussed herein) may be 40 made from an opaque material, such as fiberglass, other polymers, composites, metal, etc.

The aerator tank **105** may include an aeration assembly, and in particular, a plurality of aerator vents **400** connected together via one or more air lines **402** which may be 45 configured to receive air, e.g., compressed air, from an air source. As shown, the aerator vents **400** may be diffusers, configured to disperse air received therein. Further, the aerator vents **400** may be positioned at or proximal to a bottom **404** of the aerator tank **105**, e.g., below the level of 50 the conical clarifier **106**. However, the aerator vents **400** may not be positioned directly under the bottom **410** of the conical clarifier **106**, so as to avoid sending air into the bottom **410** of conical clarifier **106**, which may be open or otherwise in fluid communication with the aerator tank **105**. 55

The bioreactor tank **104** may further be provided with a support stand **420** for supporting the conical clarifier **106** in the aerator tank **105**. The stand **420** may be made from tubular members (e.g., PVC pipes) joined together to hold the conical clarifier **106** at a prescribed height. For example, 60 the conical clarifier **106** may be held such that its top **412** is slightly above the maximum fluid line of the aerator tank **105**.

As can also be seen in FIG. 4, the conical clarifier 106 may include an effluent outlet 430. The effluent outlet 430 65 may extend into the side of the conical clarifier 106, e.g., between the bottom 410 and the top 412 of the conical

clarifier 106. Additional details regarding embodiments of the effluent outlet 430 are discussed below.

FIG. 5 illustrates a side, elevation view of the conical clarifier **106**, according to an embodiment. As shown, the conical clarifier **106** is supported on the stand **420**. Further, as shown, the conical clarifier **106** may be truncated at its bottom **410**, rather than coming to a point. The truncated bottom **410** may include an opening, such that the interior of the conical clarifier **106** is in fluid communication with the surrounding aerator tank **105** (e.g., FIG. **4**).

Further, the effluent outlet **430** is shown, extending through the side of the conical clarifier **106**. As can be seen, the effluent outlet **430** includes an upwardly-turned end **500**. The upwardly-turned end may be configured to be received 15 into a weir, so as to prevent floating debris from exiting the conical clarifier **106**.

FIG. 6 illustrates a simplified, side, cross-sectional view of the bioreactor tank 104, according to an embodiment. As shown, influent is deposited into the aerator tank 105 via an inlet 600. The aerator vents (e.g., diffusers) 400 are positioned along the bottom 404 of the aerator tank 105, but are not positioned directly below the bottom 410 of the conical clarifier 106. As such, air bubbles emanating from the vents 400 are directed into the aerator tank 105, to agitate the influent and promote bacteria activity, but may not be directed to the bottom 410. This may prevent the bubbles, which are generally intended to agitate the fluids in the aerator tank 105, from agitating the fluid in the conical clarifier 106, despite a downwardly-facing opening 610 extending through the bottom 410 of the conical clarifier 106.

FIG. 6 also illustrates a lateral opening 620 extending through the sidewall of the conical clarifier 106. The lateral opening 620 allows for ingress of influent from the aerator tank 105 directly into the conical clarifier 106. Further, a weir 630 is provided, as mentioned above, surrounding the upwardly-turned end 500 of the effluent outlet 430. As shown, the weir 630 may be tubular and may extend downwardly, past the surface of the fluid in the conical clarifier 106, so as to prevent floating debris from entering the effluent outlet 430.

In operation, the agitated, aerated influent in the aerator tank **105** communicates with the interior of the conical clarifier **106** by way of the lateral opening **620**. Within the conical clarifier **106**, the influent is generally held quiescent, allowing for gravity-based separation of entrained solids **650** from the effluent fluid **660**. The effluent fluid **660** drains, e.g., by operation of gravity, around the weir **630** and into the effluent outlet **430**, for movement to the post-clarifying assembly discussed above. The solids **650** may drop through the downwardly-facing opening **610** and back into the aerator tank **105**, or may remain in the conical clarifier **106**.

FIG. 7 illustrates a flowchart of a method 700 for treating wastewater, according to an embodiment. The method 700 may proceed by operation of one or more embodiments of the system 100 discussed above, but in other embodiments, may be executed by one or more other systems. Furthermore, the steps of the method 700 may be executed in an order other than what is shown, or the various steps may be combined, separated, or done in parallel without departing from the scope of the present disclosure.

The method **700** may begin by receiving an influent fluid into an aerator tank **105** from a primary influent source **101**, as at **702**. However, the influent fluid may be received at one or more pre-processing tanks/structures, as desired, prior to being received into the aerator tank **105**. The method **700** may further include aerating the aerator tank **105** using a plurality of aerator vents **400** positioned proximal to a bottom **404** of the aerator tank **105**, as at **704**. The aerator vents **400** may be or include diffusers positioned along the bottom **404** of the aerator tank **105**, and may not be positioned directly below the conical clarifier **106**.

The method **700** may also include receiving at least some of the influent fluid into a conical clarifier **106** positioned within the aerator tank **105**, as at **706**. In some embodiments, the aerator vents **400** are configured to not direct air to a bottom of the conical clarifier **106**. Further, receiving the ¹⁰ influent fluid into the conical clarifier **106** may include receiving the at least some of the influent fluid through a lateral opening **620** in the conical clarifier **106** that is positioned between a bottom **410** and a top **412** of the ¹⁵ conical clarifier **106**.

The method **700** may further include separating the influent fluid in the conical clarifier **106** by gravity to generate an effluent fluid **660** and a solid waste **650**, as at **708**. The solid waste **650** may sink to the bottom **410** of the conical clarifier ²⁰ **106**. The effluent fluid **660** may be directed to an effluent outlet positioned within the conical clarifier, as at **710**. Directing the effluent fluid **660** to the effluent outlet **430** may also include using a weir **630** that surrounds the effluent outlet **430** to prevent floating sewage from entering the 25 effluent outlet **430**.

In some embodiments, the method 700 may also include directing the effluent fluid from the effluent outlet to a second clarifier, as at 720. The method 700 may further include directing the effluent fluid from the second clarifier 30 to a filter tank, as at 722. The method 700 may also include directing the effluent fluid from the filter tank to an ultraviolet (UV) filter, as at 724. The method 700 may further include sterilizing the effluent fluid using the UV filter, as at 726. The method 700 may additionally include chlorinating 35 the sterilized effluent fluid using an in-line chlorinator, as at 728. The method 700 may further include directing the sterilized, chlorinated effluent to a transfer tank, as at 730, and pumping the sterilized, chlorinated effluent into a wastewater tank, as at 732. In some embodiments, the effluent 40 fluid may not be pumped between the effluent outlet and the transfer tank, but may be moved by gravity.

The method **700** may further include receiving a secondary flow of wastewater from a secondary source **114** that is contaminated with contaminant that would inhibit bacteria 45 activity in the aerator tank **105** (e.g., hydrocarbons or bleach), as at **734**, and combining the secondary flow of wastewater with the sterilized, chlorinated effluent downstream from the wastewater tank **112**, as at **736**.

The method **700** may also include positioning the aerator 50 tank **105** and the clarifier **106** into a mobile container **350**, as at **738**. The method **700** may also include positioning a freshwater holding assembly **250** that is not in fluid communication with the aerator tank **105** into the mobile container **350**, as at **740**, and moving the mobile container with 55 the aerator tank and clarifier and the freshwater system positioned therein, as at **742**.

As used herein, the terms "inner" and "outer"; "up" and "down"; "upper" and "lower"; "upward" and "downward"; "above" and "below"; "inward" and "outward"; "uphole" 60 and "downhole"; and other like terms as used herein refer to relative positions to one another and are not intended to denote a particular direction or spatial orientation. The terms "couple," "coupled," "connect," "connection," "connected," "in connection with," and "connecting" refer to "in direct 65 connection with" or "in connection with via one or more intermediate elements or members."

The foregoing has outlined features of several embodiments so that those skilled in the art may better understand the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as 5 a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and 10 scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

What is claimed is:

1. A bioreactor for a water treatment system, the bioreactor comprising:

a tank configured to receive an influent liquid;

- a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a lower opening proximal to or at a bottom of the separator structure, wherein an interior of the separator structure is in communication with the tank, external to the separator structure, at least via the opening;
- an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not directly into the interior of the separator structure; an air line connected to the aeration vent;
- an effluent outlet communicating with the interior of the separator structure, proximal to a top of the separator structure, wherein a relatively clean effluent liquid, in comparison to the influent liquid, exits from the separator structure via the effluent outlet; and
- a stand having a base configured to receive the separator structure, wherein the stand is supported on the bottom of the tank, wherein the base of the stand is polygonal in shape and has a maximum cross-sectional dimension that is smaller than a maximum diameter of the separator structure, such that the separator structure is configured to be seated into the stand.

2. The bioreactor of claim **1**, wherein the air line extends along the bottom of the tank.

3. The bioreactor of claim **2**, wherein the air line extends through a wall of the tank, proximal to the bottom of the tank.

4. The bioreactor of claim 1, wherein the aeration vent comprises one or more diffusers extending from the bottom of the tank.

5. The bioreactor of claim 1, wherein the effluent outlet comprises a weir configured to prevent solid matter from entering into the effluent outlet.

6. The bioreactor of claim **1**, wherein the tank is configured for above-ground use.

7. The bioreactor of claim 6, wherein the bioreactor is configured to be positioned in a mobile container, such that the bioreactor is mobile.

8. The bioreactor of claim 1, wherein the separator structure comprises an inlet opening positioned above the lower opening and proximal to the top of the separator structure, but below the effluent outlet, the interior of the separator structure communicating with the tank external to the separator structure via the inlet opening.

9. A water treatment system, comprising:

a bioreactor comprising:

- a tank configured to receive an influent liquid;
- a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a downwardly-disposed opening proximal

5

10

25

35

to or at a bottom of the separator structure, wherein an interior of the separator structure is in communication with the tank, external to the separator structure, at least via the downwardly-facing opening;

an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not directly into the interior of the separator structure; an air line in communication with the aeration vent; and

- an effluent outlet communicating with the interior of the separator structure, proximal to a top of the separator structure, wherein a relatively clean effluent liquid, in comparison to the influent liquid, exits from the separator structure via the effluent outlet;
- a filter tank in fluid communication with the effluent outlet 15 of the tank;
- an ultraviolet (UV) filter in fluid communication with the filter tank;
- a chlorinator in fluid communication with the UV filter;
- a second tank and a second separator structure positioned 20 at least partially in the second tank, the second tank being in communication with the effluent outlet of the bioreactor and the filter tank; and
- a transfer tank in fluid communication with the chlorinator.

10. The system of claim **9**, further comprising a single container, wherein the bioreactor, second clarifier, filter tank, UV filter, chlorinator, and transfer tank are positioned within the single container, and wherein the single container is configured to be moved between well sites.

11. The system of claim **9**, wherein the effluent liquid is not pumped between the second tank and the transfer tank, but is moved by gravity.

12. The system of claim **9**, wherein the air line extends along the bottom of the tank.

13. The system of claim **12**, wherein the air line extends through a wall of the tank, proximal to the bottom of the tank, and wherein the aeration vent is not positioned directly below the separator structure.

14. The system of claim 12, wherein the aeration vent comprises one or more diffusers extending from the bottom of the tank.

15. The system of claim **12**, wherein the bioreactor further comprises a stand having a base configured to receive the separator structure, and wherein the stand is supported on a bottom of the tank.

16. The system of claim 15, wherein the base of the stand is polygonal in shape and has a maximum cross-sectional dimension that is smaller than a maximum diameter of the separator structure, such that the separator structure is configured to be seated into the stand.

17. A water treatment system, comprising:

a bioreactor comprising:

- a tank configured to receive an influent liquid;
- a separator structure positioned in the tank, the separator structure having a frustoconical shape and defining a downwardly-disposed opening proximal to or at a bottom of the separator structure, wherein an interior of the separator structure is in communication with the tank, external to the separator structure, at least via the downwardly-facing opening;
- an aeration vent positioned proximal to a bottom of the tank and configured to direct air into the tank, but not directly into the interior of the separator structure; an air line connected to the aeration vent; and
- an effluent outlet communicating with the interior of the separator structure, proximal to a top of the separator structure, wherein a relatively clean effluent liquid, in comparison to the influent liquid, exits from the separator structure via the effluent outlet;
- a filter tank in fluid communication with the effluent outlet of the tank;

an ultraviolet (UV) filter in fluid communication with the filter tank; and

a chlorinator in fluid communication with the UV filter, wherein the separator structure occupies a volume that is less than about ¹/₈th of a volume of the tank.

* * * * *

nk, of the tank; an ultraviolet (I